

AC-2100 PLUS

IP65 Fingerprint / Card Terminal



Features



Patented Live & Fake Finger Detection
· Optical sensor and algorithm detect fake fingers (paper, film, silicone, rubber and gelatin)



IP65 Dust / Water Resistance
· Outdoor installation



Open Supervised Device Protocol (OSDP)
· communication protocol support that allows peripheral devices to interface with control panels or other security mgmt. systems

Specification

CPU	ARM9, 400MHz CPU	Memory	32MB NOR+128MB NAND FLASH
LCD	1.77 inch Color LCD	Max Users	10,000
Power Consumption	12V, Max 400mA (4.8W)		
Communication	TCP/IP, RS485, Wiegand In/Out, USB	Log Capacity	100,000
Dimension	58 x 187.9 x 51.6 mm	Certificates	KC, CE, FCC, RoHS
RFID Card Option	125KHz-EM, 13.56MHz Smart Card, Felica, DESFire		



۰۷۱ ۳۲۲۹۴۷۰۸-۰۷۱ ۳۲۳۵۳۰۸۲
۰ ۲ ۱ ۴ ۴ ۶ ۱ ۸ ۶ ۹ ۷

۰ ۹ ۱ ۲ ۸ ۳ ۸ ۸ ۲ ۴ ۰
www.farzancard.ir